

according to Regulation (EC) No 1907/2006

### TIP TOP HARDENER No. 1 CLEAR / TIP TOP HARDENER No. 1 RED

Revision date: 23.08.2023 Product code: 00359-1065 Page 1 of 11

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

TIP TOP HARDENER No. 1 CLEAR / TIP TOP HARDENER No. 1 RED

Art.-No.

TIP TOP HARDENER No. 1 CLEAR: 590 0181, 590 0019, 590 1238

TIP TOP HARDENER No. 1 RED: 590 0356, 590 0112

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

### Use of the substance/mixture

Hardener

## 1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflaechenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg

Telephone: +49(0)3491/635-50 Telefax: +49(0)3491/635-552

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

**1.4. Emergency telephone** INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: Public Poisons Information Line: +353 (0) 1 809 2166 (8am-10pm 7 days a

week)

## **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

### Regulation (EC) No 1272/2008

Org. Perox. F; H242 Acute Tox. 3; H331 Acute Tox. 4; H302 Acute Tox. 4; H312 Asp. Tox. 1; H304 Skin Corr. 1B; H314 Carc. 1B; H350

STOT SE 3; H335 STOT RE 2; H373 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

# 2.2. Label elements

# Regulation (EC) No 1272/2008

# Hazard components for labelling

Dimethylbenzyl hydroperoxide

Cumene

2-Phenylpropan-2-ol

Signal word: Danger

Pictograms:











Print date: 23.08.2023

## **Hazard statements**

H242 Heating may cause a fire.

H302+H312 Harmful if swallowed or in contact with skin.



according to Regulation (EC) No 1907/2006

TIP TOP HARDENER No. 1 CLEAR / TIP TOP HARDENER No. 1 RED			
Revision date: 23.08.2023	Product code: 00359-1065	Page 2 of 11	

H304 May be fatal if swallowed and enters air	ways.
H314 Causes severe skin burns and eye dama	age.
H331 Toxic if inhaled.	
H335 May cause respiratory irritation.	
H350 May cause cancer.	
H373 May cause damage to organs through p	rolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

### **Precautionary statements**

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe vapour.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P273 Avoid release to the environment.

### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

Possible adverse effects: those of corticoids in general (bodyweight gain, acne, purpura and stretch marks, excitation and sleep disorders, metabolic and endocrinal disorders).

Vapours may form explosive mixture with air.

## **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

## **Chemical characterization**

Mixture containing following substances with additives:

# **Hazardous components**

CAS No	Chemical name			
	EC No	Index No	REACH No	
	GHS Classification	•		
80-15-9	Dimethylbenzyl hydroperoxide	80 - 90 %		
	201-254-7	617-002-00-8	01-2119475796-19	
	Org. Perox. E, Acute Tox. 3, A Chronic 2; H242 H331 H312 H		Corr. 1B, STOT RE 2, Aquatic	
98-82-8	Cumene	10 - 20 %		
	202-704-5	601-024-00-X	01-2119473983-24	
	Flam. Liq. 3, Carc. 1B, STOT S	E 3, Asp. Tox. 1, Aquatic Chr	onic 2; H226 H350 H335 H304 H411	
617-94-7	2-Phenylpropan-2-ol	2,5 - 5 %		
	210-539-5		01-2119965145-35	
	Acute Tox. 4, Skin Irrit. 2, Eye			

Full text of H and EUH statements: see section 16.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

### TIP TOP HARDENER No. 1 CLEAR / TIP TOP HARDENER No. 1 RED

Revision date: 23.08.2023 Product code: 00359-1065 Page 3 of 11

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Conc.	Limits, M-factors and ATE			
80-15-9	201-254-7	Dimethylbenzyl hydroperoxide			
	inhalation: LC50 = 1,4 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: LD50 = 500 mg/kg; oral: LD50 = 382 mg/kg Skin Corr. 1B; H314: >= 10 - 100 Skin Irrit. 2; H315: >= 3 - < 10 Eye Dam. 1; H318: >= 3 - < 10 Eye Irrit. 2; H319: >= 1 - < 3 STOT SE 3; H335: >= 1 - 100				
98-82-8	202-704-5	Cumene	10 - 20 %		
	inhalation: LC50 = 39 mg/l (vapours); dermal: LD50 = 12300 mg/kg				
617-94-7	210-539-5	2-Phenylpropan-2-ol	2,5 - 5 %		
	oral: ATE = 500 mg/kg				

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

### **General information**

Remove contaminated soaked clothing immediately.

Adhere to personal protective measures when giving first aid.

Symptoms of poisoning may not appear for several hours. Keep under medical supervision for at least 48 hours

#### After inhalation

Supply fresh air, if required oxygen, consult a physician.

If patient is not breathing, apply artificial respiration.

Remove the casualty into fresh air and keep him immobile.

In case of the person being unconscious put him/her in a stable side position.

# After contact with skin

Wash off immediately with soap and plenty of water.

Consult a doctor if skin irritation persists.

### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical treatment by eye specialist.

# After ingestion

Summon a doctor immediately.

Rinse out mouth and give plenty of water to drink.

Never give anything by mouth to an unconscious person.

Induce vomiting only upon the advice of a physician.

## 4.2. Most important symptoms and effects, both acute and delayed

Toxic if inhaled.

Harmful if swallowed or in contact with skin.

May be fatal if swallowed and enters airways.

Causes severe skin burns and eye damage.

May cause respiratory irritation.

May cause cancer.

May cause damage to organs through prolonged or repeated exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

# **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

### Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.



according to Regulation (EC) No 1907/2006

### TIP TOP HARDENER No. 1 CLEAR / TIP TOP HARDENER No. 1 RED

Revision date: 23.08.2023 Product code: 00359-1065 Page 4 of 11

# Unsuitable extinguishing media

Full water jet.

## 5.2. Special hazards arising from the substance or mixture

Fire may produce:

carbon monoxide and carbon dioxide

Hydrocarbons

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

#### Additional information

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

### General advice

Ensure adequate ventilation.

Keep away sources of ignition.

Keep away noninvolved persons.

## For non-emergency personnel

Do not breathe vapours.

Avoid contact with skin, eyes and clothing.

### For emergency responders

In case of vapour formation use respirator.

Use personal protective clothing.

### 6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

Inform competent authority about release into the sewerage, ground or into waters.

# 6.3. Methods and material for containment and cleaning up

### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

### For cleaning up

Shovel into suitable container for disposal.

Soak up with inert absorbent material (e.g. vermiculite, clean sand).

Dilute larger quantities of desensitization agent (e.g. fuel oil) to < 10% before disposal.

# 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Informations for disposal look up chapter 13.

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

### Advice on safe handling

Wash hands before breaks and at the end of workday.

Provide appropriate ventilation and exhaust ventilation at the workplaces.

Use only in thoroughly ventilated areas.

When using do not eat, drink or smoke.

Product may only come into contact with suitable materials, such as e.g. polyethylene or high-grade steel.

Keep away from soil, rust, chemicals, strong acids and bases and accelerators.

## Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.



according to Regulation (EC) No 1907/2006

### TIP TOP HARDENER No. 1 CLEAR / TIP TOP HARDENER No. 1 RED

Revision date: 23.08.2023 Product code: 00359-1065 Page 5 of 11

Keep away from open flames, hot surfaces and sources of ignition.

Use explosion-proof equipment / fittings and non-sparking tools.

Vapours can form an explosive mixture with air.

Avoid impact and friction.

### 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Keep only in original container.

Storage temperature between 0°C to 30°C (=32°F to 86°F).

### Hints on joint storage

Storage together with other hazardous substances is not allowed.

### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

### 7.3. Specific end use(s)

Hardener

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

### Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
98-82-8	Isopropyl benzene (cumene)	10	50		TWA (8 h)	
		50	250		STEL (15 min)	

## 8.2. Exposure controls

## Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

## Protective and hygiene measures

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

Treat subsequently with skin cream.

When using do not eat, drink or smoke.

Remove and wash contaminated clothing before re-use.

# Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

### Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: http://bestglove.com/site/chemrest/

## Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Apron (EN 467).

# Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## TIP TOP HARDENER No. 1 CLEAR / TIP TOP HARDENER No. 1 RED

Revision date: 23.08.2023 Product code: 00359-1065 Page 6 of 11

## **SECTION 9: Physical and chemical properties**

Physical state: Liquid
Colour: Clear or red
Odour: Characteristic

Test method

pH-Value: n. d.

Changes in the physical state

Melting point/freezing point:

8. n.a. Boiling point or initial boiling point and

8. n.a. n.a.

boiling range:

Sublimation point:

Softening point:

n.a.

Flash point:

64 °C

iasii poiiti.

Flammability

Solid/liquid: n.a.

## **Explosive properties**

The product is considered non-explosive; nethertheless explosive vapour/air mixture can be generated.

Lower explosion limits:n. d.Upper explosion limits:n. d.Auto-ignition temperature:n. d.

Self-ignition temperature

Solid: n.a. Gas: n.a.

Decomposition temperature: +80 °C (SADT)

**Oxidizing properties** 

Oxidizing

Vapour pressure: n. d.

(at 20 °C)

Density (at 20 °C): 1,04 g/cm³ Water solubility: n. d.

(at 20 °C)

Partition coefficient n-octanol/water: n. d.

Viscosity / dynamic: 15 mPa·s

(at 20 °C)

Viscosity / kinematic: n. d. Relative vapour density: n. d. Evaporation rate: n. d. Solvent content: < 20 %

9.2. Other information

Active oxygen: 8,3 - 8,7%

### **SECTION 10: Stability and reactivity**



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

### TIP TOP HARDENER No. 1 CLEAR / TIP TOP HARDENER No. 1 RED

Revision date: 23.08.2023 Product code: 00359-1065 Page 7 of 11

# 10.1. Reactivity

No decomposition if stored normally.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Reacts with:

Soil, rust, chemicals, strong acids and bases and accelerators (heavy metal salts, amines)

### 10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Self-Accelerating decomposition temperature (SADT) 80°C.

### 10.5. Incompatible materials

Soil, rust, chemicals, strong acids and bases and accelerators (heavy metal salts, amines)

### 10.6. Hazardous decomposition products

No hazardous decomposition products known.

Fire may produce:

Carbon monoxide and carbon dioxide

Hydrocarbons

# **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

## **Acute toxicity**

Toxic if inhaled.

Harmful if swallowed.

Harmful in contact with skin.

No toxical dates available.

### **ATEmix** calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

## Irritation and corrosivity

Causes severe skin burns and eye damage.

## Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

May cause cancer. (Cumene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

## STOT-single exposure

May cause respiratory irritation. (Dimethylbenzyl hydroperoxide; Cumene)

# STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Dimethylbenzyl hydroperoxide)

### **Aspiration hazard**

May be fatal if swallowed and enters airways.

### Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

# 11.2. Information on other hazards

## **Endocrine disrupting properties**

No data available

# Other information

Danger of perforation of the gullet and of the stomach.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

### TIP TOP HARDENER No. 1 CLEAR / TIP TOP HARDENER No. 1 RED

Revision date: 23.08.2023 Product code: 00359-1065 Page 8 of 11

## **SECTION 12: Ecological information**

# 12.1. Toxicity

Ecological dates are not available.

Toxic to aquatic life with long lasting effects.

Dimethylbenzyl hydroperoxide

LC50/Leuciscus idus = 10 - 100 mg/l

### 12.2. Persistence and degradability

No data available

### 12.3. Bioaccumulative potential

No data available

### 12.4. Mobility in soil

No data available

# 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

Hazard to waters.

Risk of drinking water contamination even when low quantities are released into the ground.

### **Further information**

Do not flush into surface water or sanitary sewer system.

# **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

### **Disposal recommendations**

In compliance with regulations by local authorities this can be subjected to a special treatment (e.g. thermal utilization) after dilution with an inert inflammable solvent (e.g. fuel oil) to 10%.

Where possible recycling is preferred to disposal.

### Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

### **SECTION 14: Transport information**

## Land transport (ADR/RID)

**14.1. UN number:** UN 3109

14.2. UN proper shipping name: ORGANIC PEROXIDE TYPE F, LIQUID (Dimethylbenzyl hydroperoxide)

14.3. Transport hazard class(es): 5.2 14.4. Packing group: -

Hazard label: 5.2+8



IRL - en

Classification code:

Limited quantity:

125 mL / 30 kg

Excepted quantity: E0



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## TIP TOP HARDENER No. 1 CLEAR / TIP TOP HARDENER No. 1 RED

Revision date: 23.08.2023 Product code: 00359-1065 Page 9 of 11

Transport category: 2
Hazard No: 539
Tunnel restriction code: D

Inland waterways transport (ADN)

**14.1. UN number:** UN 3109

14.2. UN proper shipping name: ORGANIC PEROXIDE TYPE F, LIQUID (Dimethylbenzyl hydroperoxide)

14.3. Transport hazard class(es):5.214.4. Packing group:-Hazard label:5.2+8



Classification code: P1

Limited quantity: 125 mL / 30 kg

Excepted quantity: E0

Marine transport (IMDG)

**14.1. UN number:** UN 3109

14.2. UN proper shipping name: ORGANIC PEROXIDE TYPE F, LIQUID (cumyl hydroperoxide)

14.3. Transport hazard class(es):5.214.4. Packing group:-

Hazard label: 5.2+8



Marine pollutant:

Limited quantity:

Excepted quantity:

EmS:

Yes

125 mL

E0

F-J, S-R

Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 3109

14.2. UN proper shipping name: ORGANIC PEROXIDE TYPE F, LIQUID (cumyl hydroperoxide)

14.3. Transport hazard class(es): 5.2 14.4. Packing group: -

Hazard label: 5.2+8



Limited quantity Passenger: Forbidden Passenger LQ: Forbidden Excepted quantity: E0

IATA-packing instructions - Passenger:570IATA-max. quantity - Passenger:10 LIATA-packing instructions - Cargo:570IATA-max. quantity - Cargo:25 L

14.5. Environmental hazards





# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

### TIP TOP HARDENER No. 1 CLEAR / TIP TOP HARDENER No. 1 RED

Revision date: 23.08.2023 Product code: 00359-1065 Page 10 of 11

ENVIRONMENTALLY HAZARDOUS: Yes



### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

### 14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2004/42/EC (VOC): 20 %

Information according to 2012/18/EU P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC

(SEVESO III): PEROXIDES

Additional information: E2

**National regulatory information** 

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

**Additional information** 

Consider Chemical prohibition regulation.

## 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

### **SECTION 16: Other information**

### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

### TIP TOP HARDENER No. 1 CLEAR / TIP TOP HARDENER No. 1 RED

Revision date: 23.08.2023 Product code: 00359-1065 Page 11 of 11

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Org. Perox. F; H242	Practical experience/human evidence
Acute Tox. 3; H331	Calculation method
Acute Tox. 4; H302	Calculation method
Acute Tox. 4; H312	Calculation method
Asp. Tox. 1; H304	Calculation method
Skin Corr. 1B; H314	Calculation method
Carc. 1B; H350	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 2; H411	Calculation method

## Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H242	Heating may cause a fire.
H302	Harmful if swallowed.

H302+H312 Harmful if swallowed or in contact with skin.
H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H319 Causes serious eve irritation.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H350 May cause cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

## **Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)