

according to Regulation (EC) No 1907/2006

TIP TOP REMACOAT A-80 POLY

Revision date: 18.12.2024

Product code: 00359-1091

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP REMACOAT A-80 POLY

Art.-No.

590 2921, 590 2922, 590 2940, 590 2952, 590 2960

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Coating system for protection against wear and corrosion

1.3. Details of the supplier of the safety data sheet

Company name:	TIP TOP Oberflaechenschutz Elbe GmbH	
Street:	Heuweg 4	
Place:	D-06886 Wittenberg	
Telephone:	+49(0)3491/635-50	Telefax: +49(0)3491/635-552
Responsible Department:	Responsible for the safety data sheet: sds@gb	k-ingelheim.de
1.4. Emergency telephone number:	INTERNATIONAL: +49 - (0) 6132 - 84463, GBI Public Poisons Information Line: +353 (0) 1 809 week)	· · · · · · · · · · · · · · · · · · ·

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Hazard categories: Acute toxicity: Acute Tox. 4 Skin corrosion/irritation: Skin Corr. 1B Serious eye damage/eye irritation: Eye Dam. 1 Specific target organ toxicity - repeated exposure: STOT RE 2 Hazardous to the aquatic environment: Aquatic Chronic 2 Hazard Statements: Harmful if swallowed. Causes severe skin burns and eye damage. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Glyceryl poly(oxypropylene) triamine Polyoxypropylene diamine Diethylmethylbenzenediamine

Signal word:





Hazard statements

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.



according to Regulation (EC) No 1907/2006

TIP TOP REMACOAT A-80 POLY

Revision date: 18.12.2024

Product code: 00359-1091

Page 2 of 11

Precautionary statements

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
	water of shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P308+P311	IF exposed or concerned: Call a POISON CENTER/doctor.
P405	Store locked up.
P273	Avoid release to the environment.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No	1272/2008)		
64852-22-8	Glyceryl poly(oxypropylene) triamine			< 45 %
	Skin Irrit. 2, Eye Dam. 1, Aquatic C	hronic 3; H315 H318 H412		
9046-10-0	Polyoxypropylene diamine		< 30 %	
	Acute Tox. 4, Skin Corr. 1B, Eye D	am. 1, Aquatic Chronic 3; H302 H314	4 H318 H412	
68479-98-1	Diethylmethylbenzenediamine			< 20 %
	270-877-4	612-130-00-0	01-2119486805-25	
	Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2, STOT RE 2, Aquatic Acute 1, Aquatic Chronic 1; H312 H302 H319 H373 H400 H410			
2530-83-8	3-Glycidyloxypropyl trimethoxysilane			< 5 %
	219-784-2		01-2119513212-58	
	Eye Dam. 1; H318			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
9046-10-0		Polyoxypropylene diamine	< 30 %
	dermal: LD50	= 2090 mg/kg; oral: LD50 = 475 mg/kg	
68479-98-1	270-877-4	Diethylmethylbenzenediamine	< 20 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = 598 mg/kg		
2530-83-8	219-784-2	3-Glycidyloxypropyl trimethoxysilane	< 5 %
	dermal: LD50	= 4250 mg/kg; oral: LD50 = 8025 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures



according to Regulation (EC) No 1907/2006

TIP TOP REMACOAT A-80 POLY

Revision date: 18.12.2024

Product code: 00359-1091

Page 3 of 11

General information

Remove contaminated soaked clothing immediately. Consult a physician.

Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products. In the event of symptoms refer for medical treatment.

After contact with skin

In case of contact with skin wash off immediately with plenty of water. Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Summon a doctor immediately.

After ingestion

Do not induce vomiting. Rinse out mouth and give plenty of water to drink. Never give anything by mouth to an unconscious person. Induce vomiting only upon the advice of a physician. Summon a doctor immediately.

4.2. Most important symptoms and effects, both acute and delayed

Harmful if swallowed. Causes severe skin burns and eye damage.

May cause damage to organs through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, carbon dioxide (CO2), dry chemical, water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx). Chlorine compounds

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Do not release chemically contaminated water into drains, soil or surface waters. Sufficient measures must be taken to retain water used for extinguishing.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation. Keep away noninvolved persons.



according to Regulation (EC) No 1907/2006

TIP TOP REMACOAT A-80 POLY

Revision date: 18.12.2024

Product code: 00359-1091

Page 4 of 11

For non-emergency personnel

Do not breathe vapours. Avoid contact with skin, eyes and clothing.

For emergency responders

In case of vapour formation use respirator. Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder). Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8). Informations for disposal look up chapter 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Avoid contact with the skin and the eyes. Do not breathe aerosol

Use only in thoroughly ventilated areas.

Advice on protection against fire and explosion

No special protective measures against fire required.

Advice on general occupational hygiene

Avoid contact with eyes and skin. Wash hands before breaks and immediately after handling the product. When using do not eat, drink or smoke. Remove and wash contaminated clothes before re-use. Do not inhale aerosols

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Hints on joint storage

Incompatible with acids.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Coating system for protection against wear and corrosion

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice on limit values

This product does not contain any substances for which a Workplace Exposure Limit has been set in concentrations above the limits.



according to Regulation (EC) No 1907/2006

TIP TOP REMACOAT A-80 POLY

Revision date: 18.12.2024

Product code: 00359-1091

Page 5 of 11

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: http://bestglove.com/site/chemrest/

Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour:	Viscous liquid Various
Odour:	Amine like
Changes in the physical state	
Melting point/freezing point:	n. d.
Boiling point or initial boiling point and boiling range:	n. d.
Sublimation point:	n.a.
Softening point:	n. d.
Flash point:	> 100 °C
Flammability Solid/liquid:	n.a.
Explosive properties The product is not explosive.	
Lower explosion limits:	n. d.
Upper explosion limits:	n. d.
Auto-ignition temperature:	n. d.
Self-ignition temperature	
Solid:	n.a.
Gas:	n.a.
Decomposition temperature:	n. d.
pH-Value:	n. d.
Viscosity / dynamic: (at 25 °C)	1350 - 1600 mPa·s
Viscosity / kinematic:	n. d.



according to Regulation (EC) No 1907/2006

Revision date: 18.12.2024	TIP TOP REMACOAT A-80 POLY Product code: 00359-1091	Page 6 of 1
10.12.2024	1100000.00009-1091	i age o oi i
Flow time:	n. d.	
Water solubility: (at 20 °C)	Immiscible	
Solubility in other solvents n. d.		
Partition coefficient n-octanol/water:	n. d.	
Vapour pressure:	n. d.	
Density (at 25 °C):	1,02 - 1,04 g/cm³	
Bulk density:	n.a.	
Relative vapour density:	n. d.	
9.2. Other information		
Information with regard to physical h	azard classes	
Oxidizing properties Not oxidising.		
Other safety characteristics		
Solvent separation test:	0 %	
Solvent content:	0 %	
Evaporation rate:	n. d.	
Further Information		
No data available		
SECTION 10: Stability and reactivity		
10.1. Reactivity		
No decomposition if stored and app	blied as directed.	
10.2. Chemical stability		
Stable under normal conditions.		
10.3. Possibility of hazardous reactions		
Reactions with strong acids.		
<u>10.4. Conditions to avoid</u> To avoid thermal decomposition, do	o not overheat.	
10.5. Incompatible materials Acids.		
10.6. Hazardous decomposition product No hazardous decomposition produc Fire may produce: Carbon monoxide (CO), carbon dio Chlorine compounds		
SECTION 11: Toxicological informati	on	
11.1. Information on hazard classes as d	efined in Regulation (EC) No 1272/2008	
Acute toxicity		
Harmful if swallowed.		
No toxical dates available.		
ATEmix/oral: approx. 1200 mg/kg ATEmix/dermal: > 2000 mg/kg		
ATEmix/inhalation: > 20 mg/l		

ATEmix/inhalation: > 20 mg/l



according to Regulation (EC) No 1907/2006

TIP TOP REMACOAT A-80 POLY

Revision date: 18.12.2024

Product code: 00359-1091

Page 7 of 11

Irritation and corrosivity

Serious eye damage/eye irritation: Skin corrosion/irritation: Causes severe skin burns and eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Diethylmethylbenzenediamine)

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Methaemoglobinaemia possible after skin contact.

SECTION 12: Ecological information

12.1. Toxicity

Ecological dates are not available.

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Not readily biodegradable.

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Hazard to waters.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Where possible recycling is preferred to disposal.



according to Regulation (EC) No 1907/2006

TIP TOP REMACOAT A-80 POLY

Revision date: 18.12.2024

Product code: 00359-1091

Page 8 of 11

Can be incinerated, when in compliance with local regulations.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.


SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number or ID number:</u>	UN 2735
14.2. UN proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (Polyoxypropylene diamine)
<u>14.3. Transport hazard class(es):</u>	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C7
Limited quantity:	1 L / 30 kg
Excepted quantity:	E2
Transport category:	2
Hazard No:	80
Tunnel restriction code:	E
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 2735
14.2. UN proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (Polyoxypropylene diamine)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C7
Limited quantity:	1 L / 30 kg
Excepted quantity:	E2
Marine transport (IMDG)	
14.1. UN number or ID number:	UN 2735
14.2. UN proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (Polyoxypropylene diamine,
· · · · · · · · · · · · · · · · · · ·	diethylmethylbenzenediamine)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8



according to Regulation (EC) No 1907/2006



14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information Restrictions on use (REACH, annex XVII): Entry 3	
Directive 2004/42/EC on VOC in paints and varnishes:	0 %
Information according to Directive 2012/18/EU (SEVESO III):	E2 Hazardous to the Aquatic Environment
National regulatory information	
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Water hazard class (D):	2 - obviously hazardous to water



according to Regulation (EC) No 1907/2006

TIP TOP REMACOAT A-80 POLY

Revision date: 18.12.2024

Product code: 00359-1091

Page 10 of 11

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,6,7,8,10,11,12,13,14,15.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

- RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
- ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation
 - intérieure
- IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

- CAS = Chemical Abstract Service
- EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"



according to Regulation (EC) No 1907/2006

TIP TOP REMACOAT A-80 POLY

Revision date: 18.12.2024

Product code: 00359-1091

Page 11 of 11

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)