



Safety Data Sheet

according to Regulation (EC) No 1907/2006

REMAFIX 111 COMP. B

Revision date: 21.04.2023

Product code: 00359-1277

Page 2 of 13

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P273 Avoid release to the environment.

Special labelling of certain mixtures

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture containing following substances with additives :

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

REMAFIX 111 COMP. B

Revision date: 21.04.2023

Product code: 00359-1277

Page 3 of 13

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
14808-60-7	Quartz			< 30 %
	231-545-4			
100-51-6	Benzyl alcohol			< 15 %
	202-859-9	603-057-00-5	01-2119492630-38	
	Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2; H332 H302 H319			
38294-64-3	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine			< 15 %
	500-101-4		01-2119965165-33	
	Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 3; H314 H318 H317 H412			
1477-55-0	Xylylenediamine			< 5 %
	216-032-5		01-2119480150-50	
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 3; H332 H302 H314 H318 H317 H412 EUH071			
69-72-7	salicylic acid			< 3 %
	200-712-3	607-732-00-5	01-2119486984-17	
	Repr. 2, Acute Tox. 4, Eye Dam. 1; H361d H302 H318			
13463-67-7	Titanium dioxide			< 3 %
	236-675-5	022-006-00-2	01-2119489379-17	
	Carc. 2; H351			
162627-18-1	Fatty acids, C18 unsaturated, trimers, reaction products with triethylenetetramine			< 2,5 %
	605-297-6			
	Skin Sens. 1B, Aquatic Acute 1, Aquatic Chronic 1; H317 H400 H410			
108-65-6	2-Methoxy-1-methylethyl acetate			< 2,5 %
	203-603-9	607-195-00-7	01-2119475791-29	
	Flam. Liq. 3, STOT SE 3; H226 H336			
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol			< 2,5 %
	202-013-9	603-069-00-0	01-2119560597-27	
	Acute Tox. 4, Skin Corr. 1C, Eye Dam. 1; H302 H314 H318			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

REMAFIX 111 COMP. B

Revision date: 21.04.2023

Product code: 00359-1277

Page 4 of 13

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
100-51-6	202-859-9	Benzyl alcohol	< 15 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: LD50 = 1230 mg/kg	
1477-55-0	216-032-5	Xylylenediamine	< 5 %
		inhalation: LC50 = 2,4 mg/l (vapours); dermal: LD50 = ~ 2000 mg/kg; oral: LD50 = 930 mg/kg	
69-72-7	200-712-3	salicylic acid	< 3 %
		oral: ATE = 500 mg/kg	
108-65-6	203-603-9	2-Methoxy-1-methylethyl acetate	< 2,5 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = 5155 mg/kg	
90-72-2	202-013-9	2,4,6-tris(dimethylaminomethyl)phenol	< 2,5 %
		dermal: LD50 = 1242 mg/kg; oral: LD50 = 1670 mg/kg	

Further Information

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.
Call a physician immediately.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.
If patient is not breathing, apply artificial respiration. In case of breathing difficulties give oxygen.
In the event of symptoms refer for medical treatment.

After contact with skin

In case of contact with skin wash off immediately with plenty of water.
Seek medical treatment immediately.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Remove contact lens.
Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.
Rinse out mouth and give plenty of water to drink.
Never give anything by mouth to an unconscious person.
Summon a doctor immediately.
Induce vomiting only upon the advice of a physician.
Attention. Beware, danger of aspiration.

4.2. Most important symptoms and effects, both acute and delayed

Causes severe skin burns and eye damage.
May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media



Safety Data Sheet

according to Regulation (EC) No 1907/2006

REMAFIX 111 COMP. B

Revision date: 21.04.2023

Product code: 00359-1277

Page 5 of 13

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO₂), water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation.

Keep away noninvolved persons.

For non-emergency personnel

Do not breathe vapours.

Avoid contact with skin, eyes and clothing.

For emergency responders

In case of vapour formation use respirator.

Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

Clean contaminated surface thoroughly.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Informations for disposal look up chapter 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Handle and open container with care.

Use only in thoroughly ventilated areas.

Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

No special protective measures against fire required.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

REMAFIX 111 COMP. B

Revision date: 21.04.2023

Product code: 00359-1277

Page 6 of 13

Do not use zinc, aluminium or copper containers.

Hints on joint storage

Incompatible with:

Oxidizing agents, Amines, Acids and bases.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Leveling compound

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
108-65-6	2-Methoxy-1-methylethylacetate	50	275		TWA (8 h)	
		100	550		STEL (15 min)	
1344-28-1	Aluminium oxides, respirable dust	-	4		TWA (8 h)	
7727-43-7	Barium sulphate, respirable dust	-	5		TWA (8 h)	
1477-55-0	m-Xylene alpha,alpha'-diamine (m-phenylenebis(methylamine))	-	0.1		TWA (8 h)	
14808-60-7	Quartz, respirable dust (crystalline silica)	-	0.1		TWA (8 h)	
13463-67-7	Titanium dioxide, total inhalable dust	-	10		TWA (8 h)	

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
100-51-6	Benzyl alcohol			
Worker DNEL, long-term		inhalation	systemic	22 mg/m ³
Worker DNEL, acute		inhalation	systemic	110 mg/m ³
Worker DNEL, long-term		dermal	systemic	8 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	40 mg/kg bw/day

PNEC values

CAS No	Substance	Value
100-51-6	Benzyl alcohol	
Freshwater		1 mg/l
Marine water		0,1 mg/l
Freshwater sediment		5,27 mg/kg
Marine sediment		0,527 mg/kg
Soil		0,456 mg/kg

8.2. Exposure controls**Appropriate engineering controls**

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Wash hands before breaks and immediately after handling the product.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

REMAFIX 111 COMP. B

Revision date: 21.04.2023

Product code: 00359-1277

Page 7 of 13

When using do not eat, drink or smoke.
Avoid contact with skin, eyes and clothing.
Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).
Eye wash bottle with pure water (EN 15154).

Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.
This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.
Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.
Pls. find examples in the protective gloves database under: <http://bestglove.com/site/chemrest/>

Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Pasty	
Colour:	White	
Odour:	Characteristic	
pH-Value:		n.d.

Changes in the physical state

Melting point/freezing point:		n.d.
Boiling point or initial boiling point and boiling range:		n.d.
Sublimation point:		n.d.
Softening point:		n.d.
Pour point:		n.d.
Flash point:	> 100 °C	

Flammability

Solid/liquid:		n.a.
---------------	--	------

Explosive properties

The product is not explosive.

Lower explosion limits:		n.d.
Upper explosion limits:		n.d.
Auto-ignition temperature:		n.d.

Self-ignition temperature

Solid:		n.a.
Gas:		n.a.

Decomposition temperature:		n.d.
----------------------------	--	------

Oxidizing properties

Not oxidising.

Vapour pressure:		n.d.
------------------	--	------

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

REMAFIX 111 COMP. B

Revision date: 21.04.2023

Product code: 00359-1277

Page 8 of 13

Density (at 20 °C):	1,90 g/cm ³
Bulk density:	n.a.
Water solubility: (at 20 °C)	Immiscible
Solubility in other solvents n.d.	
Partition coefficient n-octanol/water:	n.d.
Viscosity / dynamic:	Pasty
Viscosity / kinematic:	n.d.
Flow time:	n.d.
Relative vapour density:	n.d.
Evaporation rate:	n.d.
Solvent separation test:	n.d.
Solvent content:	n.d.

9.2. Other information

No data available

SECTION 10: Stability and reactivity**10.1. Reactivity**

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidising agents.

10.4. Conditions to avoidTo avoid thermal decomposition, do not overheat.
Protect against direct sun radiation.**10.5. Incompatible materials**

Oxidizing agents, Amines, Acids and bases.

10.6. Hazardous decomposition productsNo hazardous decomposition products known.
Fire may produce:
Carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x)
Ammonia**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**Based on available data, the classification criteria are not met.
No toxicological data available.**Irritation and corrosivity**Causes severe skin burns and eye damage.
Causes serious eye damage.**Sensitising effects**

May cause an allergic skin reaction. (4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine; Xylylenediamine; Fatty acids, C18 unsaturated, trimers, reaction products with triethylenetetramine)

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

REMAFIX 111 COMP. B

Revision date: 21.04.2023

Product code: 00359-1277

Page 9 of 13

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards**Endocrine disrupting properties**

No data available

SECTION 12: Ecological information**12.1. Toxicity**

Ecological data are not available.

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

Not readily biodegradable.

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Hazard to waters.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

REMAFIX 111 COMP. B

Revision date: 21.04.2023


Product code: 00359-1277

Page 10 of 13


Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information


Land transport (ADR/RID)

14.1. UN number:	UN 2735
14.2. UN proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8 
Classification code:	C7
Special Provisions:	274
Limited quantity:	1 L / 30 kg
Excepted quantity:	E2
Transport category:	2
Hazard No:	80
Tunnel restriction code:	E

Inland waterways transport (ADN)

14.1. UN number:	UN 2735
14.2. UN proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8 
Classification code:	C7
Special Provisions:	274
Limited quantity:	1 L / 30 kg
Excepted quantity:	E2

Marine transport (IMDG)

14.1. UN number:	UN 2735
14.2. UN proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8 
Marine pollutant:	No

Safety Data Sheet

according to Regulation (EC) No 1907/2006

REMAFIX 111 COMP. B

Revision date: 21.04.2023

Product code: 00359-1277

Page 11 of 13

Special Provisions: 274
Limited quantity: 1 L / 30 kg
Excepted quantity: E2
EmS: F-A, S-B
Segregation group: 18 - alkalis

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 2735
14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine)
14.3. Transport hazard class(es): 8
14.4. Packing group: II
Hazard label: 8



Special Provisions: A3 A803
Limited quantity Passenger: 0.5 L
Passenger LQ: Y840
Excepted quantity: E2
IATA-packing instructions - Passenger: 851
IATA-max. quantity - Passenger: 1 L
IATA-packing instructions - Cargo: 855
IATA-max. quantity - Cargo: 30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2004/42/EC (VOC): 0 %

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

REMAFIX 111 COMP. B

Revision date: 21.04.2023

Product code: 00359-1277

Page 12 of 13

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,12.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
 RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
 ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
 IMDG = International Maritime Code for Dangerous Goods
 IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
 MARPOL = International Convention for the Prevention of Pollution from Ships
 IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
 CAS = Chemical Abstract Service
 EN = European norm
 ISO = International Organization for Standardization
 DIN = Deutsche Industrie Norm
 PBT = Persistent Bioaccumulative and Toxic
 vPvB = Very Persistent and very Bio-accumulative
 LD = Lethal dose
 LC = Lethal concentration
 EC = Effect concentration
 IC = Median immobilisation concentration or median inhibitory concentration

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

REMAFIX 111 COMP. B

Revision date: 21.04.2023

Product code: 00359-1277

Page 13 of 13

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)