

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP REMAPUR BIO COMP A

Revision date: 09.01.2024

Product code: 00156-0535

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP REMAPUR BIO COMP A

Art.-No.

7691010

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Repair material

1.3. Details of the supplier of the safety data sheet

Company name: REMA TIP TOP AG

Street: Gruber Strasse 65

Place: D-85586 Poing

Telephone: +49 (0) 8121 / 707 - 100

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
Public Poisons Information Line: +353 (0) 1 809 2166 (8am-10pm 7 days a week)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Acute Tox. 4; H332

Skin Irrit. 2; H315

Eye Irrit. 2; H319

Resp. Sens. 1; H334

Skin Sens. 1; H317

Carc. 2; H351

STOT SE 3; H335

STOT RE 2; H373

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Polypropylene glycol, diphenylmethane diisocyanate polymer


Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl) phenyl isocyanate

4,4'-Methylene-diphenyl diisocyanate

o-(p-isocyanatobenzyl)phenyl isocyanate

Signal word: Danger

Pictograms:



Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP REMAPUR BIO COMP A

Revision date: 09.01.2024

Product code: 00156-0535

Page 2 of 12

H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P201	Obtain special instructions before use.
P260	Do not breathe vapour.
P264	Wash skin thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P308+P313	IF exposed or concerned: Get medical advice/attention.

Special labelling of certain mixtures

EUH204	Contains isocyanates. May produce an allergic reaction. As from 24 August 2023 adequate training is required before industrial or professional use.
--------	--

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Preparation with isocyanates

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
39420-98-9	Polypropylene glycol, diphenylmethane diisocyanate polymer			< 70 %
	Resp. Sens. 1, Skin Sens. 1; H334 H317			
26447-40-5	Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl) phenyl isocyanate			< 50 %
	247-714-0	615-005-00-9	01-2120770510-62	
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373			
101-68-8	4,4'-Methylene-diphenyl diisocyanate			< 15 %
	202-966-0	615-005-00-9	01-2119457014-47	
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373			
5873-54-1	o-(p-isocyanatobenzyl)phenyl isocyanate			< 15 %
	227-534-9	615-005-00-9	01-2119480143-45	
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP REMAPUR BIO COMP A

Revision date: 09.01.2024

Product code: 00156-0535

Page 3 of 12

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
26447-40-5	247-714-0	Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl) phenyl isocyanate	< 50 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: LD50 = 9200 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100 Resp. Sens. 1; H334: >= 0,1 - 100 STOT SE 3; H335: >= 5 - 100	
101-68-8	202-966-0	4,4'-Methylene-diphenyl diisocyanate	< 15 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: LC50 = 0,368 mg/l (dusts or mists); dermal: LD50 = > 9400 mg/kg; oral: LD50 = > 2000 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100 Resp. Sens. 1; H334: >= 0,1 - 100 STOT SE 3; H335: >= 5 - 100	
5873-54-1	227-534-9	o-(p-isocyanatobenzyl)phenyl isocyanate	< 15 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: LC50 = 0,31 mg/l (dusts or mists); dermal: LD50 = > 9400 mg/kg; oral: LD50 = > 2000 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100 Resp. Sens. 1; H334: >= 0,1 - 100 STOT SE 3; H335: >= 5 - 100	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

- Remove contaminated soaked clothing immediately.
- In the event of persistent symptoms receive medical treatment.
- Take away from danger area and lay down affected person.

After inhalation

- If patient is not breathing, apply artificial respiration.
- Move to fresh air in case of accidental inhalation of vapours.
- Refer for medical treatment.

After contact with skin

- Remove immediately adhering matter.
- Consult a physician.
- Wash contaminated skin with plenty of water and soap or with liquid polyethylene glycol.

After contact with eyes

- Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
- Seek medical treatment by eye specialist.

After ingestion

- Do not induce vomiting.
- Rinse out mouth thoroughly with water. Never give anything by mouth to an unconscious person.
- Summon a doctor immediately.
- Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

- Harmful if inhaled.
- Causes skin irritation.
- May cause an allergic skin reaction.
- Causes serious eye irritation.
- May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- May cause respiratory irritation.
- Suspected of causing cancer.
- May cause damage to organs through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

- Keep under medical supervision for at least 48 hours.

SECTION 5: Firefighting measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP REMAPUR BIO COMP A

Revision date: 09.01.2024

Product code: 00156-0535

Page 4 of 12

5.1. Extinguishing media

Suitable extinguishing media

Foam, carbon dioxide (CO₂), dry chemical, water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x).

Hydrogen cyanide (HCN)

Isocyanates (NCO).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Do not release chemically contaminated water into drains, soil or surface waters. Sufficient measures must be taken to retain water used for extinguishing.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation.

Remove persons to safety.

For non-emergency personnel

Do not breathe vapours.

Avoid contact with skin, eyes and clothing.

For emergency responders

In case of vapour formation use respirator.

Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

No not container for disposal.

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Informations for disposal look up chapter 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Vapours are heavier than air and spread along ground.

Avoid contact with the skin and the eyes.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP REMAPUR BIO COMP A

Revision date: 09.01.2024

Product code: 00156-0535

Page 5 of 12

Do not breathe vapours.
Local exhaust.
Use only in thoroughly ventilated areas.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep containers tightly closed in a cool, well-ventilated place.

Keep at temperatures between 15°C and 35°C.

Hints on joint storage

Exothermic reaction with:

Acids and bases.

Water, amines, alcohols

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

7.3. Specific end use(s)

Repair material

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
101-68-8	4,4'-Methylene-diphenyl diisocyanate (as -NCO)	0.005	-		TWA (8 h)	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP REMAPUR BIO COMP A

Revision date: 09.01.2024

Product code: 00156-0535

Page 6 of 12

DNEL/DMEL values

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
5873-54-1	o-(p-isocyanatobenzyl)phenyl isocyanate		
Worker DNEL, acute	dermal	systemic	50 mg/kg bw/day
Worker DNEL, acute	inhalation	systemic	0,1 mg/m ³
Worker DNEL, acute	dermal	local	28,7 mg/cm ²
Worker DNEL, acute	inhalation	local	0,1 mg/m ³
Worker DNEL, long-term	dermal	systemic	0 mg/kg bw/day
Worker DNEL, long-term	inhalation	systemic	0,05 mg/m ³
Worker DNEL, long-term	dermal	local	0 mg/cm ²
Consumer DNEL, acute	dermal	systemic	25 mg/kg bw/day
Consumer DNEL, acute	inhalation	systemic	0,05 mg/m ³
Consumer DNEL, acute	oral	systemic	20 mg/kg bw/day
Consumer DNEL, acute	dermal	local	17,2 mg/cm ²
Consumer DNEL, long-term	dermal	local	0 mg/cm ²
Consumer DNEL, long-term	dermal	systemic	0 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,025 mg/m ³
Consumer DNEL, long-term	oral	systemic	0 mg/kg bw/day
Consumer DNEL, long-term	inhalation	local	0,025 mg/m ³
Worker DNEL, long-term	inhalation	local	0,05 mg/m ³

PNEC values

CAS No	Substance	
Environmental compartment	Value	
5873-54-1	o-(p-isocyanatobenzyl)phenyl isocyanate	
Freshwater	> 1 mg/l	
Marine water	> 0,1 mg/l	
Micro-organisms in sewage treatment plants (STP)	> 1 mg/l	
Soil	> 1 mg/kg	

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Take off immediately all contaminated clothing.

Eye/face protection

Eye wash bottle with pure water (EN 15154).

Tightly fitting goggles (EN 166).

Hand protection

Protective gloves resistant to chemicals made off butyl, Minimum coat thickness 0,7 mm, Permeation resistance (wear duration) > 240 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP REMAPUR BIO COMP A

Revision date: 09.01.2024

Product code: 00156-0535

Page 7 of 12

carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	Yellow	
Odour:	Characteristic	
pH-Value:		n.a.

Changes in the physical state

Melting point/freezing point:		n. d.
Boiling point or initial boiling point and boiling range:		n. d.
Sublimation point:		n.a.
Softening point:		n. d.
Flash point:	> 100 °C	

Flammability

Solid/liquid:		n.a.
---------------	--	------

Explosive properties

The product is not explosive.

Lower explosion limits:		n. d.
Upper explosion limits:		n. d.
Auto-ignition temperature:		n. d.

Self-ignition temperature

Solid:		n.a.
Gas:		n.a.
Decomposition temperature:		n. d.

Oxidizing properties

Not oxidising.

Vapour pressure: (at 25 °C)	< 0,00001 hPa	
Density (at 20 °C):	1,10 - 1,14 g/cm ³	
Bulk density:		n.a.
Water solubility: (at 20 °C)	Reacts with water	

Solubility in other solvents

n. d.

Partition coefficient n-octanol/water:		n. d.
Viscosity / dynamic: (at 25 °C)	850 - 1600 mPa·s	
Viscosity / kinematic:		n. d.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP REMAPUR BIO COMP A

Revision date: 09.01.2024

Product code: 00156-0535

Page 8 of 12

Flow time:	n. d.
Relative vapour density:	8,5
Evaporation rate:	n. d.
Solvent separation test:	0 %
Solvent content:	0 %

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with strong acids and alkalies.

Reacts with: Water, amines, alcohols

10.4. Conditions to avoid

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

10.5. Incompatible materials

Acids and bases

Water, amines, alcohols

10.6. Hazardous decomposition products

Fire may produce:

Hydrogen cyanide gas.

Carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x)

Isocyanates

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

No toxicological data available.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) 10,78 mg/l; ATE (inhalation dust/mist) 1,471 mg/l

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

May cause allergy or asthma symptoms or breathing difficulties if inhaled. (Polypropylene glycol, diphenylmethane diisocyanate polymer; Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl) phenyl isocyanate; 4,4'-Methylene-diphenyl diisocyanate; o-(p-isocyanatobenzyl)phenyl isocyanate)

May cause an allergic skin reaction. (Polypropylene glycol, diphenylmethane diisocyanate polymer; Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl) phenyl isocyanate; 4,4'-Methylene-diphenyl diisocyanate; o-(p-isocyanatobenzyl)phenyl isocyanate)

Contains isocyanates. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP REMAPUR BIO COMP A

Revision date: 09.01.2024

Product code: 00156-0535

Page 9 of 12

Suspected of causing cancer. (Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl) phenyl isocyanate; 4,4'-Methylene-diphenyl diisocyanate; o-(p-isocyanatobenzyl)phenyl isocyanate)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl) phenyl isocyanate; 4,4'-Methylene-diphenyl diisocyanate; o-(p-isocyanatobenzyl)phenyl isocyanate)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl) phenyl isocyanate; 4,4'-Methylene-diphenyl diisocyanate; o-(p-isocyanatobenzyl)phenyl isocyanate)

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

12.2. Persistence and degradability

Not readily biodegradable.

12.3. Bioaccumulative potential

A bioaccumulation potential is to be expected.

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Slightly water hazardous.

Further information

In aqueous systems, formation of insoluble and chemically inert (inactive) polyureas.

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

List of Wastes Code - residues/unused products

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP REMAPUR BIO COMP A

Revision date: 09.01.2024

Product code: 00156-0535

Page 10 of 12

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 56, Entry 74, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes: 0 %

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP REMAPUR BIO COMP A

Revision date: 09.01.2024

Product code: 00156-0535

Page 11 of 12

Information according to Directive 2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

1 - slightly hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information**Abbreviations and acronyms**

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
MARPOL = International Convention for the Prevention of Pollution from Ships
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
CAS = Chemical Abstract Service
EN = European norm
ISO = International Organization for Standardization
DIN = Deutsche Industrie Norm
PBT = Persistent Bioaccumulative and Toxic
vPvB = Very Persistent and very Bio-accumulative
LD = Lethal dose
LC = Lethal concentration
EC = Effect concentration
IC = Median immobilisation concentration or median inhibitory concentration

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H332	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Resp. Sens. 1; H334	Calculation method
Skin Sens. 1; H317	Calculation method
Carc. 2; H351	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 2; H373	Calculation method

Relevant H and EUH statements (number and full text)

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP REMAPUR BIO COMP A

Revision date: 09.01.2024

Product code: 00156-0535

Page 12 of 12

H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH204	Contains isocyanates. May produce an allergic reaction.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)