

## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

### **TIP TOP SOLVENT CF-CE**

Revision date: 16.11.2023 Product code: 00156-0233 Page 1 of 11

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

TIP TOP SOLVENT CF-CE

Art.-No.

595 9163, 595 9175, 356 1811

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Cleaning agent

### 1.3. Details of the supplier of the safety data sheet

Company name: REMA TIP TOP AG
Street: Gruber Strasse 65
Place: D-85586 Poing

Telephone: +49 (0) 8121 / 707 - 100

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

<u>1.4. Emergency telephone</u> INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a) Public Poisons Information Line: +353 (0) 1 809 2166 (8am-10pm 7 days a

week)

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

# Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H336 Aquatic Acute 1; H400 Aquatic Chronic 1; H410

Full text of hazard statements: see SECTION 16.

## 2.2. Label elements

### Regulation (EC) No 1272/2008

# Hazard components for labelling

Ethyl acetate Cyclohexane

Signal word: Danger

Pictograms:









# **Hazard statements**

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.



## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

### **TIP TOP SOLVENT CF-CE**

Revision date: 16.11.2023 Product code: 00156-0233 Page 2 of 11

### **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing vapour.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P273 Avoid release to the environment.

#### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

### **Chemical characterization**

Mixture of solvents

#### **Hazardous components**

CAS No	Chemical name				
	EC No	Index No	REACH No		
	GHS Classification	•			
141-78-6	Ethyl acetate			< 55 %	
	205-500-4	607-022-00-5	01-2119475103-46		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066				
110-82-7	Cyclohexane			< 55 %	
	203-806-2	601-017-00-1	01-2119463273-41		
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H225 H315 H336 H304 H400 H410				

Full text of H and EUH statements: see section 16.

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

### General information

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

Take away from danger area and lay down affected person.

# After inhalation

Move to fresh air in case of accidental inhalation of vapours.

Seek medical treatment immediately.



## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

#### **TIP TOP SOLVENT CF-CE**

Revision date: 16.11.2023 Product code: 00156-0233 Page 3 of 11

#### After contact with skin

Wash off with soap and plenty of water.

Consult a doctor if skin irritation persists.

#### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical treatment by eye specialist.

#### After ingestion

Do not induce vomiting.

Summon a doctor immediately.

Induce vomiting only upon the advice of a physician.

#### 4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

#### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media

Foam, carbon dioxide (CO2), dry chemical, water-spray.

#### Unsuitable extinguishing media

Full water jet.

### 5.2. Special hazards arising from the substance or mixture

Fire may produce:

carbon monoxide and carbon dioxide

# 5.3. Advice for firefighters

Use breathing apparatus with independent air supply.

Protective suit.

#### **Additional information**

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

### General advice

Ensure adequate ventilation.

Keep away noninvolved persons.

# For non-emergency personnel

Do not breathe vapours.

Avoid contact with skin, eyes and clothing.

### For emergency responders

In case of vapour formation use respirator.

Use personal protective clothing.

Use only explosion-proof equipment.

#### 6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.



according to Regulation (EC) No 1907/2006

#### **TIP TOP SOLVENT CF-CE**

Revision date: 16.11.2023 Product code: 00156-0233 Page 4 of 11

### 6.3. Methods and material for containment and cleaning up

#### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

#### For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

### 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Informations for disposal look up chapter 13.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

# Advice on safe handling

Keep container tightly closed.

Vapours are heavier than air and spread along ground.

Keep a good ventilation and air-exhaust at the place of work.

Avoid contact with skin, eyes and clothing.

#### Advice on protection against fire and explosion

Do not smoke - volatile.

Keep away from heat and sources of ignition.

Take precautionary measures against static discharges.

Use only explosion-proof equipment.

#### 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Pay attention to anti-explosion rules.

# Hints on joint storage

Incompatible with oxidizing agents.

# Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

### 7.3. Specific end use(s)

Cleaning agent

### **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

### Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
110-82-7	Cyclohexane	200	700		TWA (8 h)	
141-78-6	Ethyl acetate	200	734		TWA (8 h)	
		400	1468		STEL (15 min)	

### 8.2. Exposure controls

### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

# Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.



according to Regulation (EC) No 1907/2006

### **TIP TOP SOLVENT CF-CE**

Revision date: 16.11.2023 Product code: 00156-0233 Page 5 of 11

When using do not eat, drink or smoke.

Treat subsequently with skin cream.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothes before re-use.

### Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

#### Hand protection

Splash protection:

Protective gloves resistant to chemicals made off butyl, Minimum coat thickness 0,7 mm, Permeation resistance (wear duration) > 30 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374

carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

#### Skin protection

Solvent-resistant apron (EN 467).

#### Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: Colourless
Odour: Fruity

pH-Value: n.a.

Changes in the physical state

Melting point/freezing point: < - 30 °C
Boiling point or initial boiling point and > 76 °C

boiling range:

Sublimation point:

Softening point:

n. d.

Flash point:

Sustaining combustion:

Sustaining combustion

**Flammability** 

Solid/liquid: n.a.

# **Explosive properties**

The product is considered non-explosive; nethertheless explosive vapour/air mixture can be generated.

Lower explosion limits: approx. 1,2 vol. % Upper explosion limits: approx. 11,5 vol. % Auto-ignition temperature: 260 °C

Self-ignition temperature

Solid: n.a. Gas: n.a.
Decomposition temperature: n. d.

### **Oxidizing properties**

Not oxidising.



according to Regulation (EC) No 1907/2006

### **TIP TOP SOLVENT CF-CE**

Revision date: 16.11.2023 Product code: 00156-0233 Page 6 of 11

Vapour pressure: 104 hPa

(at 20 °C)

Density (at 20 °C): approx. 0,83 g/cm³
Bulk density: n.a.
Water solubility: Immiscible

(at 20 °C)

Solubility in other solvents

n. d.

Partition coefficient n-octanol/water:

Niscosity / dynamic:

Niscosity / kinematic:

1. d.

Niscosity / kinematic:

1. d.

20,5 mm²/s

(at 40 °C)

Flow time:

Relative vapour density:

n. d.
Solvent separation test:

n. d.
Solvent content:

100 %

#### 9.2. Other information

No data available

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No decomposition if stored and applied as directed.

### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Reactions with oxidising agents.

### 10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Vapour/air mixtures are explosive at intensive warming.

Heating can release vapours which can be ignited.

# 10.5. Incompatible materials

Strong oxidizing agents

### 10.6. Hazardous decomposition products

No hazardous decomposition products known.

Fire may produce:

Carbon monoxide and carbon dioxide

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

Based on available data, the classification criteria are not met.

No toxical dates available.

Ethyl acetate

LD50/oral/rat: 4935 mg/kg LC50/inhalativ/rat: 1600 mg/l

Cyclohexane

LD50/oral/rat: 12705 mg/kg



## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

#### **TIP TOP SOLVENT CF-CE**

Revision date: 16.11.2023 Product code: 00156-0233 Page 7 of 11

#### **ATEmix** calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

# Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause drowsiness or dizziness. (Ethyl acetate; Cyclohexane)

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

May be fatal if swallowed and enters airways.

#### Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

### 11.2. Information on other hazards

#### **Endocrine disrupting properties**

No data available

### Other information

May cause irritation of the mucous membranes.

Effects of breathing high concentrations of vapour may include.

Headache, dizziness, weakness, unconsciousness.

#### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Ecological dates are not available.

Very toxic to aquatic life with long lasting effects.

Cyclohexane

EC50/Daphnia magna/48 h = 0,9 mg/l

IC50/Selenastrum capricornutum/72 h > 4 mg/l

### 12.2. Persistence and degradability

No data available

# 12.3. Bioaccumulative potential

No data available

### 12.4. Mobility in soil

No data available

# 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

Hazard to waters.

### **Further information**

Do not flush into surface water or sanitary sewer system.



according to Regulation (EC) No 1907/2006

### **TIP TOP SOLVENT CF-CE**

Revision date: 16.11.2023 Product code: 00156-0233 Page 8 of 11

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### **Disposal recommendations**

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

### List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

### Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

# **SECTION 14: Transport information**

#### Land transport (ADR/RID)

**14.1. UN number:** UN 1993

**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (Cyclohexane, Ethyl acetate)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1

Special Provisions: 274 601 640D Limited quantity: 1 L / 30 kg

Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

### Inland waterways transport (ADN)

**14.1. UN number:** UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Cyclohexane, Ethyl acetate)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1

Special Provisions: 274 601 640D Limited quantity: 1 L / 30 kg Excepted quantity: E2



according to Regulation (EC) No 1907/2006

### **TIP TOP SOLVENT CF-CE**

Revision date: 16.11.2023 Product code: 00156-0233 Page 9 of 11

Marine transport (IMDG)

**14.1. UN number:** UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (cyclohexane and ethyl acetate)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Marine pollutant: Yes
Special Provisions: 274
Limited quantity: 1 L / 30 kg
Excepted quantity: E2
EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (cyclohexane and ethyl acetate, solution)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Excepted quantity:

A3

1 L

Y341

Excepted quantity:

E2

IATA-packing instructions - Passenger:353IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Print date: 16.11.2023

# 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

### 14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

# **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulatory information

Restrictions on use (REACH, annex XVII): Entry 3, Entry 40, Entry 57, Entry 75

2004/42/EC (VOC): 100 %



according to Regulation (EC) No 1907/2006

#### **TIP TOP SOLVENT CF-CE**

Revision date: 16.11.2023 Product code: 00156-0233 Page 10 of 11

Information according to 2012/18/EU

(SEVESO III):

P5c FLAMMABLE LIQUIDS

Additional information:

**National regulatory information** 

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

E1

#### **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 12.

#### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 1; H410	Calculation method

#### Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

	TIP TOP SOLVENT CF-CE	
Revision date: 16.11.2023	Product code: 00156-0233	Page 11 of 11

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### **Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)