

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP SOLVENT LIQUID BUFFER

Revision date: 03.06.2022

Product code: 00156-0008

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP SOLVENT LIQUID BUFFER

Art.-No.

505 9685, 505 9702, 505 9719, 505 9740, 507 9706, 511 1190, 514 4870, 599 2200, 356 1810

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaning agent

1.3. Details of the supplier of the safety data sheet

Company name: REMA TIP TOP AG

Street: Gruber Strasse 65

Place: D-85586 Poing

Telephone: +49 (0) 8121 / 707 - 100

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
Public Poisons Information Line: +353 (0) 1 809 2166 (8am-10pm 7 days a week)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225

Asp. Tox. 1; H304

Skin Irrit. 2; H315

STOT SE 3; H336

Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Naphtha (petroleum)

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing vapour.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243 Take action to prevent static discharges.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP SOLVENT LIQUID BUFFER

Revision date: 03.06.2022

Product code: 00156-0008

Page 2 of 10

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331 Do NOT induce vomiting.
P273 Avoid release to the environment.
P391 Collect spillage.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Preparation solved in petroleum spirit

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
64742-49-0	Naphtha (petroleum) [Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane]	> = 75 %		
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
64742-49-0	Naphtha (petroleum) [Hydrocarbons, C6, isoalkanes, < 3% n-hexane]	<= 25 %		
	931-254-9		01-2119484651-34	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			

Full text of H and EUH statements: see section 16.

Further Information

According to note P to the directive 67/548/EEC, "Naphtha (petroleum)" is not to be classified as "carcinogenic" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.
In the event of persistent symptoms receive medical treatment.
Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.
If you feel unwell, seek medical advice.

After contact with skin

Wash off with soap and plenty of water.
Consult a doctor if skin irritation persists.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP SOLVENT LIQUID BUFFER

Revision date: 03.06.2022

Product code: 00156-0008

Page 3 of 10

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.
Summon a doctor immediately.
Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.
May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways. Attention. Beware, danger of aspiration.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, carbon dioxide (CO₂), dry chemical, water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:
carbon monoxide and carbon dioxide

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.
Protective suit.

Additional information

Vapours are heavier than air and spread along ground.
The vapour/air mixture is explosive, even in empty, uncleaned receptacles.
Cool containers at risk with water spray jet.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation.
Keep away noninvolved persons.

For non-emergency personnel

Do not breathe vapours.
Avoid contact with skin, eyes and clothing.

For emergency responders

In case of vapour formation use respirator.
Use personal protective clothing.
Use only explosion-proof equipment.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP SOLVENT LIQUID BUFFER

Revision date: 03.06.2022

Product code: 00156-0008

Page 4 of 10

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).
Informations for disposal look up chapter 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.
Vapours are heavier than air and spread along ground.
Use only in thoroughly ventilated areas.
Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

Do not smoke - volatile.
Keep away from heat and sources of ignition.
Take precautionary measures against static discharges.
Use only explosion-proof equipment.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.
Pay attention to anti-explosion rules.

Hints on joint storage

Incompatible with oxidizing agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Cleaning agent

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.
Wash hands before breaks and immediately after handling the product.
When using do not eat, drink or smoke.
Treat subsequently with skin cream.
Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Hand protection

Protective gloves resistant to chemicals made off nitrile, Minimum coat thickness 0.4 mm, Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril Velours 730> made by



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP SOLVENT LIQUID BUFFER

Revision date: 03.06.2022

Product code: 00156-0008

Page 5 of 10

www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Solvent-resistant apron (EN 467).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	Colourless	
Odour:	Hydrocarbon-like	

Test method

pH-Value: n.a.

Changes in the physical state

Melting point/freezing point:	n. d.	
Boiling point or initial boiling point and boiling range:	60 - 95 °C	ASTM D1078
Sublimation point:	n.a.	
Softening point:	n. d.	
Flash point:	- 25 °C	
Sustaining combustion:	Sustaining combustion	

Flammability

Solid/liquid:	n.a.
Gas:	n.a.

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated

Lower explosion limits:	1,0 vol. %
Upper explosion limits:	7,3 vol. %
Auto-ignition temperature:	413 °C

Self-ignition temperature

Solid:	n.a.
Gas:	n.a.

Decomposition temperature: n. d.

Oxidizing properties

Not oxidising.

Vapour pressure: 150 hPa
(at 20 °C)

Density (at 15 °C): 0,693 g/cm³ DIN 51757

Bulk density: n.a.

Water solubility: 0,02 g/L
(at 20 °C)

Solubility in other solvents

n. d.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP SOLVENT LIQUID BUFFER

Revision date: 03.06.2022

Product code: 00156-0008

Page 6 of 10

Partition coefficient n-octanol/water:	(n-octanol/water) Log Pow: 4 - 5,1
Viscosity / dynamic:	0,45 mPa·s
Viscosity / kinematic: (at 40 °C)	< 20,5 mm ² /s
Flow time:	n. d.
Relative vapour density:	n. d.
Evaporation rate:	7,6 ASTM D 3539
Solvent separation test:	0 %
Solvent content:	100 %

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with oxidising agents.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.
Vapour/air mixtures are explosive at intensive warming.
Heating can release vapours which can be ignited.

10.5. Incompatible materials

Oxidizing agents

10.6. Hazardous decomposition products

No hazardous decomposition products known.
Fire may produce:
Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.
LD50/oral/rat: > 2000 mg/kg
LD50/dermal/rabbit: > 2000 mg/kg
LC50/inhalativ/rat: > 20 mg/l

Irritation and corrosivity

Causes skin irritation.
Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Naphtha (petroleum) [Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane]; Naphtha (petroleum) [Hydrocarbons, C6, isoalkanes, < 3% n-hexane])



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP SOLVENT LIQUID BUFFER

Revision date: 03.06.2022

Product code: 00156-0008

Page 7 of 10

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Hazard of lung oedema.

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Contact with eyes may cause irritation.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

SECTION 12: Ecological information

12.1. Toxicity

Naphtha (petroleum)

EC50/Daphnia: 1 - 10 mg/l

EC50/Algae: 10 - 100 mg/l

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

The product is readily biodegradable to OECD criteria.

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Slightly water hazardous.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

List of Wastes Code - residues/unused products

140603 WASTE ORGANIC SOLVENTS, REFRIGERANTS AND PROPELLANTS (EXCEPT 07 AND 08); waste organic solvents, refrigerants and foam/aerosol propellants; other solvents and solvent mixtures; hazardous waste

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP SOLVENT LIQUID BUFFER

Revision date: 03.06.2022

Product code: 00156-0008

Page 8 of 10

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	UN 1263
14.2. UN proper shipping name:	Paint related material
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3



Classification code:	F1
Limited quantity:	5 L / 30 kg
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number:	UN 1263
14.2. UN proper shipping name:	Paint related material
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3



Classification code:	F1
Limited quantity:	5 L / 30 kg
Excepted quantity:	E2

Marine transport (IMDG)

14.1. UN number:	UN 1263
14.2. UN proper shipping name:	Paint related material (Naphtha (petroleum))
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3



Marine pollutant:	Yes
Limited quantity:	5 L / 30 kg
Excepted quantity:	E2
EmS:	F-E, S-E

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP SOLVENT LIQUID BUFFER

Revision date: 03.06.2022

Product code: 00156-0008

Page 9 of 10

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	UN 1263
14.2. UN proper shipping name:	Paint related material
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3



Limited quantity Passenger:	1 L
Passenger LQ:	Y341
Excepted quantity:	E2
IATA-packing instructions - Passenger:	353
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

2004/42/EC (VOC):	95 - 100 %
Information according to 2012/18/EU (SEVESO III):	P5c FLAMMABLE LIQUIDS
Additional information:	E2

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,6,7,9,10,11,12,14,15.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP SOLVENT LIQUID BUFFER

Revision date: 03.06.2022

Product code: 00156-0008

Page 10 of 10

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
IMDG = International Maritime Code for Dangerous Goods
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
MARPOL = International Convention for the Prevention of Pollution from Ships
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
CAS = Chemical Abstract Service
EN = European norm
ISO = International Organization for Standardization
DIN = Deutsche Industrie Norm
PBT = Persistent Bioaccumulative and Toxic
vPvB = Very Persistent and very Bio-accumulative
LD = Lethal dose
LC = Lethal concentration
EC = Effect concentration
IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.
The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.
The delivery specifications are contained in the corresponding product sheet.
This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.
"(n.a. = not applicable; n.d. = not determined)"

'The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)