

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP SOLVENT T-200

Revision date: 15.10.2024 Product code: 00359-1261 Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP SOLVENT T-200

Art.-No.

590 0610, 590 0611, 590 0612

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaning agent

1.3. Details of the supplier of the safety data sheet

TIP TOP Oberflaechenschutz Elbe GmbH Company name:

Street: Heuweg 4

D-06886 Wittenberg Place:

Telephone: +49(0)3491/635-50 Telefax: +49(0)3491/635-552

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a) number:

Public Poisons Information Line: +353 (0) 1 809 2166 (8am-10pm 7 days a

week)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Acute Tox. 4: H312 Acute Tox. 4; H332 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Eye Irrit. 2; H319

STOT SE 3; H335 H336 STOT RE 2; H373 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Reaction mass of ethylbenzene and xylene

Ethyl acetate Propan-2-ol

Hydrocarbons, C6-C7, isoalkanes, cycloalkanes, < 3% n-hexane

Signal word: Danger

Pictograms:







Hazard statements

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways. H312+H332 Harmful in contact with skin or if inhaled.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP SOLVENT T-200				
Revision date: 15.10.2024	Product code: 00359-1261	Page 2 of 12		
H335	May cause respiratory irritation.			
H319	Causes serious eye irritation.			
H315	Causes skin irritation.			
H336	May cause drowsiness or dizziness.			
H373	May cause damage to organs through prolonged or repeated exposure.			
H412	Harmful to aquatic life with long lasting effects.			
Precautionary statemen	nts			
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No			

smoking.

P260 Do not breathe vapour.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P273 Avoid release to the environment.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of organic solvents



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP SOLVENT T-200

Revision date: 15.10.2024 Product code: 00359-1261 Page 3 of 12

Hazardous components

CAS No	Chemical name			
	EC No	Index No	REACH No	
	Classification (Regulation	n (EC) No 1272/2008)	•	
	Reaction mass of ethylbe	enzene and xylene		< 45 %
	905-588-0		01-2119488216-32	
	· ·	4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit 2 H315 H319 H335 H373 H304	. 2, STOT SE 3, STOT RE 2, Asp.	
141-78-6	ethyl acetate			< 30 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2,	066		
64-17-5	Ethanol		< 15 %	
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2;			
67-63-0	Propan-2-ol	< 15 %		
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2,			
92062-15-2	Hydrocarbons, C6-C7, is	< 10 %		
	926-605-8		01-2119486291-36	
	Flam. Liq. 2, STOT SE 3			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
Specific Conc. Limits, M-factors and ATE			
	905-588-0	Reaction mass of ethylbenzene and xylene	< 45 %
inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg STOT RE 2; H373: >= 10 - 100			
64-17-5	200-578-6	Ethanol	< 15 %
	Eye Irrit. 2; H31	9: >= 50 - 100	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.

In the event of symptoms refer for medical treatment.

After contact with skin

Wash off immediately with soap and plenty of water.

Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Consult (eye) doctor immediately.

After ingestion

Do not induce vomiting.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP SOLVENT T-200

Revision date: 15.10.2024 Product code: 00359-1261 Page 4 of 12

Rinse out mouth and give plenty of water to drink.

Never give anything by mouth to an unconscious person.

Summon a doctor immediately.

The decision whether to induce vomiting or not is to be taken by a physician.

4.2. Most important symptoms and effects, both acute and delayed

Harmful in contact with skin or if inhaled.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:

carbon monoxide and carbon dioxide

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.

Protective suit.

Additional information

Vapours are heavier than air and spread along ground.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation.

Keep away sources of ignition.

Keep away noninvolved persons.

For non-emergency personnel

Avoid contact with skin, eyes and clothing.

Do not breathe vapours.

For emergency responders

In case of vapour formation use respirator.

Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP SOLVENT T-200

Revision date: 15.10.2024 Product code: 00359-1261 Page 5 of 12

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

Clean contaminated surface thoroughly.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Informations for disposal look up chapter 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Use only in area provided with appropriate exhaust ventilation.

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

Advice on protection against fire and explosion

Keep product and empty container away from heat and sources of ignition.

Pay attention to anti-explosion rules.

Do not smoke.

Take precautionary measures against static discharges.

Advice on general occupational hygiene

Do not inhale vapours.

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Remove and wash contaminated clothes before re-use.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep containers tightly closed in a cool, well-ventilated place.

Keep away from heat and sources of ignition.

Hints on joint storage

Incompatible with oxidizing agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Cleaning agent

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
64-17-5	Ethyl alcohol	1000	-		STEL (15 min)	
100-41-4	Ethylbenzene	100	442		TWA (8 h)	
		200	884		STEL (15 min)	
67-63-0	Propan-2-ol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	
1330-20-7	Xylene, mixed isomers	50	221		TWA (8 h)	
		100	442		STEL (15 min)	



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP SOLVENT T-200

Revision date: 15.10.2024 Product code: 00359-1261 Page 6 of 12

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
100-41-4	Ethyl benzene	Ethylbenzene	0	End-exhaled air	Not critical

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Pay attention to explosion protection rules.

Individual protection measures, such as personal protective equipment

Eve/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Splash protection:

Protective gloves resistant to chemicals made off butyl, Minimum coat thickness 0,7 mm, Permeation resistance (wear duration) > 30 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: Colourless
Odour: Characteristic

Changes in the physical state

Melting point/freezing point:

Boiling point or initial boiling point and boiling range:

Sublimation point:

n. d.

n. d.

n. d.

point or initial boiling point and boiling point and boiling range:

Sublimation point:

Softening point:

n.a.

n. d.

Flash point:

- 6 °C

Flammability

Solid/liquid: n.a.

Explosive properties

The product is considered non-explosive; nethertheless explosive vapour/air mixture can be generated.

Lower explosion limits: n. d. Upper explosion limits: n. d. Auto-ignition temperature: n. d.

Self-ignition temperature

Solid: n.a. Gas: n.a.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIF	P TOP SOLVENT T-200	
Revision date: 15.10.2024	Product code: 00359-1261	Page 7 of 12
Decomposition temperature:	n. d.	
pH-Value:	n. d.	
Viscosity / dynamic:	n. d.	
Viscosity / kinematic: (at 40 °C)	< 20,5 mm²/s	
Flow time:	n. d.	
Water solubility:	Immiscible	
Solubility in other solvents n. d.		
Partition coefficient n-octanol/water:	n. d.	
Vapour pressure: (at 20 °C)	n. d.	
Density (at 20 °C):	0,842 g/cm ³	
Bulk density:	n.a.	
Relative vapour density:	n. d.	
9.2. Other information		
Information with regard to physical hazard classe		
Sustaining combustion:	Sustaining combustion	
Oxidizing properties Not oxidising.		
Other safety characteristics		
Solvent separation test:	0 %	
Solvent content:	100 %	
Evaporation rate:	n. d.	
Further Information		
No data available		

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with oxidising agents.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Vapours may form explosive mixture with air.

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

No hazardous decomposition products known.

Fire may produce:

Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP SOLVENT T-200

Revision date: 15.10.2024 Product code: 00359-1261 Page 8 of 12

Acute toxicity

Harmful in contact with skin.

Harmful if inhaled.

No toxical dates available.

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Reaction mass of ethylbenzene and xylene)

May cause drowsiness or dizziness. (ethyl acetate)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Reaction mass of ethylbenzene and xylene)

Aspiration hazard

May be fatal if swallowed and enters airways.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

Inhalation of high vapour concentration may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

SECTION 12: Ecological information

12.1. Toxicity

Ecological dates are not available.

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Hazard to waters.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP SOLVENT T-200

Revision date: 15.10.2024 Product code: 00359-1261 Page 9 of 12

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken

Packaging that cannot be cleaned should be disposed of like the product.

Empty containers should be taken for local recycling, recovery or waste disposal.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Ethyl acetate, Propan-2-ol)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1

Limited quantity: 1 L / 30 kg
Excepted quantity: F2

Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Ethyl acetate, Propan-2-ol)

 14.3. Transport hazard class(es):
 3

 14.4. Packing group:
 II

 Hazard label:
 3



Classification code: F1

Limited quantity: 1 L / 30 kg
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1993



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP SOLVENT T-200

Revision date: 15.10.2024 Product code: 00359-1261 Page 10 of 12

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Ethylacetate, Propan-2-ol)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Marine pollutant: No

Limited quantity: 1 L / 30 kg
Excepted quantity: E2
EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Ethylacetate, Propan-2-ol, Solution)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2

IATA-packing instructions - Passenger:353IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in 100 %

paints and varnishes:

Information according to Directive P5c FLAMMABLE LIQUIDS

2012/18/EU (SEVESO III):

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

Print date: 15.10.2024

nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP SOLVENT T-200

Revision date: 15.10.2024 Product code: 00359-1261 Page 11 of 12

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,6,7,9,10,11,12,14,15.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Acute Tox. 4; H312	Calculation method
Acute Tox. 4; H332	Calculation method
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H335	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H312+H332 Harmful in contact with skin or if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP SOLVENT T-200				
Revision date: 15.10.2024	Product code: 00359-1261	Page 12 of 12		
H335	May cause respiratory irritation.			
H336	May cause drowsiness or dizziness.			
H373	May cause damage to organs through prolonged or repeated exposure.			
H411	Toxic to aquatic life with long lasting effects.			
H412	Harmful to aquatic life with long lasting effects.			
EUH066	Repeated exposure may cause skin dryness or cracking.			

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)